



## OPERADORA JUNO S.A. DE C.V.

Azafrán No. 200, Col. Granjas México, C.P. 08400, Ciudad de México, México.  
Tel: 55-5657-9498 contacto@kumatrade.com

### Hilo de látex con Silicón- Especificaciones Técnicas

V2022-10

CALIBRE	DIÁMETRO MM	ÁREA MM <sup>2</sup>	RENDIMIENTO M / KG	RENDIMIENTO YDS / LBS	DENIER
20	1.270	1.267	775	316	11611
22	1.155	1.047	938	383	9596
23	1.104	0.958	1025	418	8779
24	1.058	0.880	1116	456	8063
25	1.016	0.811	1211	494	7431
26	0.977	0.750	1310	535	6870
28	0.907	0.647	1519	620	5924
30	0.847	0.563	1744	712	5160
32	0.794	0.495	1984	810	4535
34	0.747	0.439	2240	914	4018
36	0.706	0.391	2511	1025	3584
37	0.686	0.370	2653	1083	3392
38	0.668	0.351	2798	1142	3216
40	0.635	0.317	3101	1266	2903
42	0.605	0.287	3418	1395	2633
44	0.577	0.262	3752	1531	2399
46	0.552	0.240	4100	1674	2195
48	0.529	0.220	4465	1823	2016
50	0.508	0.203	4845	1978	1858
52	0.488	0.187	5240	2139	1718
54	0.470	0.174	5651	2307	1593
55	0.462	0.168	5862	2393	1535
56	0.454	0.162	6077	2481	1481
60	0.423	0.141	6976	2848	1290
63	0.403	0.128	7691	3140	1170
65	0.391	0.120	8187	3342	1099
70	0.363	0.103	9495	3876	948
75	0.339	0.090	10900	4450	826
80	0.318	0.079	12402	5063	726
85	0.299	0.070	14001	5715	643
90	0.282	0.063	15697	6407	573
100	0.254	0.051	19378	7910	464
105	0.242	0.046	21365	8721	421
110	0.231	0.042	23448	9571	384
125	0.203	0.032	30279	12360	297
TOLERANCIA	± 2.5 %	± 5 %	± 5 %	± 5 %	± 5 %